

Technical Specification:

Television Coaxial, Data and Telephone Sockets



CATEGORY:

TV/DATA/TELEPHONE SOCKETS

Insert Ref:

09/1	1 gang Non-Isolated Coaxial 1 in/1 Out
09/2	2 gang Non-Isolated Coaxial 2 in/2 Out
10/1	1 gang Isolated Coaxial 1 in/1 Out
10/2	Isolated TV/FM Diplexer 1 in/2 Out
11/1	1 gang telephone Master
11/2	1 gang telephone Slave

EUROFIX TV/DATA/TELEPHONE SOCKET MODULES

Insert Ref:

CM009	1 gang Non-Isolated Coaxial 1 in /1 Out
CM010	1 gang Isolated Coaxial 1 in/ 1 Out
CM032	Isolated TV/FM Diplexer 1 in/2 Out
CM046	1 gang Satellite
CM037	1 gang RJ11 Outlet
CM014	1 gang RJ45 CAT 5E Outlet
CM016	1 gang RJ45 CAT 6 Outlet
CM111	1 gang Telephone Master
CM112	1 gang Telephone Slave
CM033	Triplex TV/FM/SAT
CM034	Quadplex FM/TV2 x SAT

TECHNICAL SPECIFICATION:

IP Rating:	IP2XD
Product Class 1:	Must be earthed
Ambient operating Temperature:	-5 to +40 C
Location:	Internal Use Only
Max Installation Altitude	2000m

Note: Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box a suitable barrier MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.

Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush wall boxes

BS EN ISO Standard BS EN 60669-1

	1mm ²	1.5mm ²	2.5mm ²	4mm ² Multi-Strand	6mm ²
Earth Terminal Capacity	5	4	3	1	1

Plate Fixing Centres:

Single Plate - 60.3mm 09/1, 09/2, 10/1, 10/2, 11/1, 11/2

Twin Plate - 120.6mm