

Technical Specification: Asbury Period Switch Collection



CATEGORY:

10AX ROCKER SWITCH

Insert Ref:

01-1	1 gang 10AX Toggle
01-2	2 gang 10AX Toggle
01-3	3 gang 10AX Toggle
01-4	4 gang 10AX Toggle
01-1-INT	1 gang 10AX Intermediate Toggle

10AX RETRACTIVE TOGGLE SWITCH

Insert Ref:

01-1-PTM	1 gang 10AX Push to Make/Break Retractive Toggle
----------	--

TECHNICAL SPECIFICATION:

Voltage:	220/250V AC	Location:	Internal Use Only
IP Rating:	IP2XD	Max Installation Altitude	2000m
Switched Poles:	Single	Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush wall boxes	
Contact Gap Minimum	3mm		
Product Class 1:	Must be earthed		
Ambient operating Temperature:	-5 to +40 C		
		BS EN ISO Standard	BS EN 60669-1

	1mm ²	1.5mm ²	2.5mm ²	4mm ² Multi-Strand	8mm ²
Terminal Capacity	5	4	2	2	1
Earth Terminal Capacity	6	5	2	2	1

Plate Fixing Centres:

Single Plate - 60.3mm 01-1, 01-2V, 01-3V, 01-1-INT,

Twin Plate - 120.6mm 01-2H, 01-3H, 01-4,