## **Technical Specification:**Dimmer Switches



CATEGORY:

**DIMMER SWITCH** 

Insert Ref:

20-1 1 gang 400W Dimmer
20-2 2 gang 400W Dimmer
19-2 2 gang 250W Dimmer
19-3 3 gang 250W Dimmer
19-4 4 gang 250W Dimmer

## **TECHNICAL SPECIFICATION:**

Voltage: 220/250V AC Maximum Load Rating: Halogen; 400W or 250W

Maximum Current Rating: 1.7A

Product Class 1: Must be earthed

Ambient operating Temperature: -5 to +40 C

Intended Applications: Indoor use only. Domestic

lighting circuits.

Ideal for incandescent lighting including mains

and low voltage halogen.

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm<sup>2</sup> Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm<sup>2</sup>

Location: Internal Use Only

Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush

wall boxes

BS EN ISO Standard BS EN 60669-2-1

**Safety Advice:** Not suitable for wire-wound low voltage transformers, fluorescent lighting, motors or fans. Do not overload. Product must be earthed.

## **Plate Fixing Centres:**

Single Plate - 60.3mm 20-1, 20-2, 19-2

Twin Plate - 120.6mm 19-3, 19-4

Please Note that due to constant changes in regulations the user should satisfy themselves that there have been no recent amendments

E&0E 06/16