

# Technical Specification: Period Toggle Switches



## CATEGORY:

### 20AX ROCKER SWITCH

Insert Ref:

PT8/1	1 gang 20AX Toggle
PT8/2	2 gang 20AX Toggle
PT8/3	3 gang 20AX Toggle
PT8/4	4 gang 20AX Toggle
PT8/INT	1 gang 20AX Intermediate Toggle

### 10AX RETRACTIVE TOGGLE SWITCH

Insert Ref:

PT8/PTM	1 gang 10AX Push to Make/Break Retractive Toggle
---------	--

## TECHNICAL SPECIFICATION:

Voltage:	220/250V AC	Location:	Internal Use Only
IP Rating:	IP2XD	Max Installation Altitude	2000m
Switched Poles:	Single	Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush wall boxes	
Contact Gap Minimum	3mm		
Product Class 1:	Must be earthed		
Ambient operating Temperature:	-5 to +40 C		
		BS EN ISO Standard	BS EN 60669-1

	1mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup> Multi-Strand	8mm <sup>2</sup>
Terminal Capacity	5	4	2	2	1
Earth Terminal Capacity	6	5	2	2	1

## Plate Fixing Centres:

Single Plate - 60.3mm PT8/1, PT8/2, PT8/INT, PT8/PTM

Twin Plate - 120.6mm PT8/3, PT8/4