Technical Specification: Rocker Switches



CATEGORY: <u>10AX ROCKER SWITCH</u> Insert Ref: 01/1 1 gang 10AX 2 way Rocker 01/2 2 gang 10AX 2 way Rocker 01/3 3 gang 10AX 2 way Rocker 01/4 4 gang 10AX 2 way Rocker 01/6 6 gang 10AX 2 way Rocker 02/1 1 gang 10AX Intermediate Rocker

TECHNICAL SPECIFICATION:

Voltage:	220/250V AC	Location:	Internal Use Only	
IP Rating:	IP2XD	Max Installation Altitude	2000m	
Switched Poles:	Single			
Contact Gap Minimum	3mm	Standard Switch to Wood electrical accessories are		
Product Class 1:	Must be earthed	designed to be mounted onto BS4662-2006 flush		
Ambient operating Temperature: -5 to +40 C		wall boxes		

BS EN ISO Standard

BS EN 60669-1

	1mm ^²	1.5mm ²	2.5 mm ²	4mm ² Multi-Strand	8mm²
Terminal Capacity 10AX	5	4	1	1	1
Earth Terminal Capacity 10AX	5	4	3	1	1
Terminal Capacity 20AX	5	4	2	2	1
Earth Terminal Capacity 20AX	6	5	2	2	1

Plate Fixing Centres:

Single Plate - 60.3mm 01/1, 01/2, 01/3, 02/1

Twin Plate - 120.6mm 01/4, 01/6

Please Note that due to constant changes in regulations the user should satisfy themselves that there have been no recent amendments

E&OE 06/16