

# Technical Specification: Unswitched Sockets



## CATEGORY:

### 2AMP UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current rating: 2 Amp  
 Max Load: 2 Amp  
 Insert Ref:  
 07/1 1 gang 2A Unswitched Socket

### 13A UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current Rating: 13 Amp  
 Max Load: 13 Amp  
 Insert Ref:  
 131 1 gang 13A Unswitched Socket  
 132 2 gang 13A Unswitched Socket

### 5AMP UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current Rating: 5 Amp  
 Max Load: 5 Amp  
 Insert Ref:  
 07/2 1 gang 5A Unswitched Socket

## TECHNICAL SPECIFICATION:

Voltage:	220/250V AC	Location:	Internal Use Only
IP Rating:	IP2XD	Max Installation Altitude	2000m
Switched Poles:	None		
Contact Gap Minimum	None	Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush wall boxes	
Product Class 1:	Must be earthed		
Ambient operating Temperature:	-5 to +40 C		
Shuttered	Yes		

BS EN ISO Standard	
2A and 5A Unswitched	BS 546
13A Unswitched	BS 1363-2

	1mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup>	6mm <sup>2</sup> Multi-Strand	10mm <sup>2</sup>
2A and 5A Terminal Capacity	5	4	2	1		
2A and 5A Earth Terminal Capacity	5	4	2	1		
13A Terminal Capacity			3	3	2	1
13A Earth Terminal Capacity			3	3	2	1

## Plate Fixing Centres:

Single Plate - 60.3mm 07/1, 07/2, 131

Twin Plate - 120.6mm 132